

# C25C

IC-CUSHION      LPG/DUAL FUEL  
 4000 / 5000 / 6000 / 6500 lbs.  
 (2000 / 2500 / 3000 / 3200 kg)

GEN2



## STANDARD SPECIFICATIONS

## C20/25/30/32C

| Manufacturer's Designation                        |              | C20CL                        | C25CL                        | C30CL                        | C32CL                        |
|---|--------------|------------------------------|------------------------------|------------------------------|------------------------------|
| Load Capacity / Rated Load                        | lbs(kg)      | 4000 (2000)                  | 5000 (2500)                  | 6000 (3000)                  | 6500 (3200)                  |
| Height Overhead Guard                             | in(mm)       | 82.8 (2105)                  | 82.8 (2105)                  | 82.8 (2105)                  | 82.8 (2105)                  |
| Width   | in(mm)       | 42.5 (1080)                  | 42.5 (1080)                  | 43.7 (1110)                  | 45.4 (1154)                  |
| Right Angle Stack (add load length and clearance) | in(mm)       | 94.5 (2399)                  | 96.8 (2459)                  | 99.2 (2519)                  | 101.4 (2575)                 |
| Outside Turning Radius                            | in(mm)       | 77.8 (1975)                  | 134.6 (3420)                 | 82.3 (2090)                  | 83.9 (2130)                  |
| Travel speed loaded / unloaded                    | mph (kph)    | 10.0 / 10.1 (16.1 / 16.2)    | 10.0 / 10.1 (16.1 / 16.2)    | 10.0 / 10.1 (16.1 / 16.2)    | 10.0 / 10.1 (16.1 / 16.2)    |
| Engine / Rated output per SAE J1349               | HP(KW) @ rpm | Hyundai / 70.4 (52.5) @ 2650 | Hyundai / 70.4 (52.5) @ 2650 | Hyundai / 70.4 (52.5) @ 2650 | Hyundai / 70.4 (52.5) @ 2650 |

## STANDARD FEATURES

**2.4 liter engine • EPA compliant • Electronic governor • Fuel system diagnostics • Low LPG warning light • Standard, Triple, Hi-Lo and Quad uprights • Full range of lift heights available • High visibility “silent staging” uprights • Automatic engine shutdown protection • Two-pedal inch-brake system • High capacity cooling system • Auxiliary valve • Routine maintenance points are highly accessible • Isolated operator cell • Clark safety seat • Tilt steering wheel • Clark Information Center, full LED/digital display • Full access clamshell hood • Headlights - overhead guard mounted**

